

SELECTING THE RIGHT MATERIAL FOR YOUR DOT PLACARD NEEDS

Presented By: Bill Sargent

theGHSstore.com

 176 # tagboard with glossy film laminate on one side

NO minimum application temp

Service temp range is -20 degrees to +200 degrees F



- Designed for single trip/temporary applications (priced accordingly) (ground domestic shipments)
- NOT intended for international
- Placard holder is needed
- Color-Matched UV inks, coated back for enhanced moisture resistance





REMOVABLE ADHESIVE VINYL

 4 mil flexible vinyl with removable adhesive

32 degree Fminimum application temp

Service temp range is -20 degrees to +200 degrees F



- Designed for single trip/temporary applications (ground domestic shipments)
- NOT intended for international
- Placard holder is NOT needed
- Clean removal up to 3 months LOOK **FOR**

PERM. ADHESIVE VINYL

 4 mil flexible film with permanent acrylic adhesive

0 degrees F minimum application temp

Service temp range is -40 degrees to +200 degrees F



- Designed for permanent applications (International, Rail, Storage Tanks)
- Intended for international; BS 5609 certified
- Placard holder is NOT needed
- MDG 90-day sea water immersion LOOK test, UV inks, acrylic adhesives with FOR superior chemical resistance

 20 mil HDPE Plastic blend (no adhesive)

NO minimum application temp

Service temp range is -30 degrees to +200 degrees F



- Designed for permanent applications (International, Rail, Storage Tanks)
- Intended for international; BS 5609 certified
- Placard holder IS needed
- Color-Matched UV inks, Look non-tearing, superior chemical resistance









